



## FT06-2W

FT06 Series



## Fused Terminals & Connectors

FT06 - / 83 (A)-

Blank: Without Fuse  
F2A: With 2A Fuse  
F3A: With 3A Fuse

### Metal Parts

Blank: Brass clamping unit  
W: Brass clamping unit + wire protector  
GW: Brass clamping unit + wire protector + earthing screw

Number of Connection Points: 1-5

### Structure of Housing

Blank: No anti-rotation spigot  
P: With anti-rotation spigot

Item No.		FT06-2W	
Electrical Data			
IEC/EN			
		Fuse Holder	Terminal
Rated Voltage (V)		250	450
Rated Current (A)		6.3	15
Ambient Temperature	Polyamide 66	105°C	
Connection Data			
		IEC/EN	
Cross Section	Solid conductor	2.5-4.0mm <sup>2</sup>	
	Stranded conductor	2.5-4.0mm <sup>2</sup>	
	Flexible conductor	2.5-4.0mm <sup>2</sup>	
Strip length (mm)		7	
Means of connection		screw fixed	
Screw		M3	
Rewirable		√	
Number of terminals		multiway	
Number of connection points		2	
Means of Fixing			
screw fixed			
Materials			
Insulation Materials	Designation	Polyamide 66	
	Flammability class	UL 94V-2	
Clamping Unit		brass, stainless steel (wire protector)	
Compatible Products			
Fuse		5*20mm fuse	
Packing Quantity (pcs/carton)			
700			

FT06-2W

